

## SNMP/Web Interface Card, Remote Cooling Management

MODEL NUMBER: SRCOOLNET2



Installs inside select Tripp Lite air conditioning units to let you monitor temperatures, receive alerts, review logs and control settings over the Ethernet network from any location via SNMP, SSH, telnet or web browser.

### Description

The SRCOOLNET2 SNMP/Web Interface Card adds remote monitoring and management capabilities to select Tripp Lite air conditioning units, including the SRCOOL7KRM. By installing the SRCOOLNET2 into the unit's accessory slot, you will be able to control the cooling unit over the Ethernet network from any location via SNMP, SSH, telnet or web browser. Monitor temperatures, adjust fan speed, and activate dehumidification modes. You can also review logs remotely and receive alerts. LEDs confirm network connection, speed and card initialization. The included ENVIROSENSE® module connects to the SRCOOLNET2's PS/2 port to monitor temperatures and humidity up to 12 feet away from the primary unit, allowing its operation to be based on the intake air temperature where the sensor is mounted. The ENVIROSENSE also lets you monitor smoke detectors, fire alarms and security systems through a dry-contact interface.

### Features

#### Control Your Cooling Unit from Anywhere

- Turn select in-rack (such as Tripp Lite SRCOOL7KRM) and portable air conditioning units into a managed network device
- Access unit via SNMP, SSH, telnet or web browser
- Monitor temperatures
- Adjust fan speed
- Activate dehumidification modes
- Review logs
- Receive alerts

### Highlights

- Enables remote management of Tripp Lite air conditioning unit
- Controls temperature, fan speed and dehumidification modes
- Sends alerts in case of power failure, high temperature, etc.
- Installs easily in unit's accessory slot
- Includes ENVIROSENSE temperature and humidity sensor

### Package Includes

- SRCOOLNET2 SNMP/Web Interface Card
- ENVIROSENSE module
- Configuration cable (73-1025)
- MAC address label (located on SRCOOLNET2)
- Owner's Manuals



- LEDs confirm network connection/speed and card initialization

#### **Includes ENVIROSENSE Temperature/Humidity Sensor Module**

- Monitors temperature and humidity up to 12 ft. away
- Controls smoke detectors, fire alarms and security systems via dry-contact interface
- Connects easily to SRCOOLNET2's PS/2 port

#### **Easy to Set Up and Manage**

- Installs easily into cooling unit's front SNMP accessory slot
- Included PowerAlert® software interface provides single display for controlling cooling units and ENVIROSENSE modules
- Compliant with the Federal Trade Agreements Act (TAA) for GSA Schedule purchases

## **Specifications**

<b>OVERVIEW</b>	
UPC Code	037332188793
Accessories Type	SNMP Card Module
<b>INPUT</b>	
Nominal Input Voltage Description	12V DC
<b>USER INTERFACE, ALERTS &amp; CONTROLS</b>	
LED Indicators	1 Link LED to confirm connection and indicate speed and 1 Status LED to indicate when the card is initialized
<b>PHYSICAL</b>	
Shipping Dimensions (hwd / in.)	2.280 x 6.500 x 6.930
Shipping Dimensions (hwd / cm)	5.79 x 16.51 x 17.60
Shipping Weight (lbs.)	0.4000
Shipping Weight (kg)	0.18
<b>WARRANTY</b>	
Product Warranty Period (Worldwide)	2-year limited warranty

© 2018 Tripp Lite. All rights reserved. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Tripp Lite uses primary and third-party agencies to test its products for compliance with standards. See a list of Tripp Lite's testing agencies:



**Tripp Lite**  
1111 W. 35th Street  
Chicago, IL 60609 USA  
Telephone: 773.869.1234  
[www.tripplite.com](http://www.tripplite.com)

<https://www.tripplite.com/products/product-certification-agencies>