


## Female insert - VS-MSTBAH 2,5/ 5-GB-5,08-BK-A - 1657915

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

MSTB contact insert, for PCB assembly, 24 V, 5-pos., with angled solder pins, RAL 9005 (black), for panel mounting frame VS-PPC-F2-MSTB-...-1R-P



### Key commercial data

Packing unit	1 PCE
Minimum order quantity	50 PCE
GTIN	 4 046356 132497
Custom tariff number	85366990
Country of origin	GERMANY

### Technical data

#### Mechanical characteristics

Number of positions	5
Insertion/withdrawal cycles	≥ 100
Connection method	Printed circuit connection
Color	black
Ambient temperature (operation)	-40 °C ... 70 °C

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
---------------------------------	------------------

#### Material data

Inflammability class according to UL 94	V0
Contact carrier material	PBT
Contact material	Copper alloy
Contact surface material	Gold over nickel

#### Electrical characteristics

Number of positions	5
Rated current	16 A

# Female insert - VS-MSTBAH 2,5/ 5-GB-5,08-BK-A - 1657915

## Classifications

### ETIM

ETIM 3.0	EC000438
ETIM 4.0	EC000438
ETIM 5.0	EC000438

### UNSPSC

UNSPSC 11	31261501
UNSPSC 12.01	31261501
UNSPSC 13.2	31261501
UNSPSC 6.01	31261501
UNSPSC 7.0901	31261501

### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701
eCl@ss 5.1	27260701
eCl@ss 6.0	27261204
eCl@ss 7.0	27440205
eCl@ss 8.0	27440205

## Approvals

### Approvals

---

#### Approvals

UL Recognized / cUL Recognized / GOST / cULus Recognized

---

#### Ex Approvals

---

#### Approvals submitted

---

### Approval details

# Female insert - VS-MSTBAH 2,5/ 5-GB-5,08-BK-A - 1657915

## Approvals

UL Recognized	
Nominal current I <sub>N</sub>	16 A
Nominal voltage U <sub>N</sub>	24 V

cUL Recognized	
Nominal current I <sub>N</sub>	16 A
Nominal voltage U <sub>N</sub>	24 V

GOST	
------	--

cULus Recognized	
------------------	--

## Accessories

### Accessories

#### Panel mounting frames - VS-PPC-F2-MSTB-MNNA-1R-P - 1608087



MSTB panel mounting frame, IP67, for push-pull interlocking, metal, for PCB connection, for square panel cutout, with grommet, without mounting screws

#### Panel mounting frames - VS-PPC-F2-MSTB-POBK-1R-P - 1608281




MSTB panel mounting frame, IP67, for push-pull interlocking, plastic, for PCB connection, for square panel cutout, with grommet, without mounting screws

# Female insert - VS-MSTBAH 2,5/ 5-GB-5,08-BK-A - 1657915

## Accessories


## Drawings

Drilling diagram



Drilling diagram

Dimensioned drawing



MSTB contact insert