

	ω		A					
4	m				4			
	11-				4			
	1 16							
		1						
		1						
	1	2						
		1						
					3			
S EXA	AMPLE							
any	non-conformit	ty or damage						
	which does not comply with							
er of the Parties or by a third party ndation, technical notice.)								
untry FR	Jurisd	liction & Cont Not Listed	rol List		2			
	1]				
3K	35SN							
]				
				MOD N°				
		CUSTOME	RDRAWING					
Stee	el Recepta	icle 8D se	ries					
ar		NPRDS /	PROJECT					
		8	59		1			
		This doc	ument is the prop SOURIAU	perty of				
it must not be reproduced or								
		communi	icated without pe					
	DRG N°			SHEET				
К3	5SN-C			1/2	J			
	В		А					

Image: Constraint of the state of the s								
		т	Q	нт —	m		0	
		Contact Layout Par						
	4							
c μη μαριο μα		position ID X-axis (mm) 1 -428 (10.4) 2 -467 (11.4) 3 -486 (12.4) 4 -415 (10.1) 5 -488 (12.4) 6 -428 (10.4) 7 -428 (10.4) 8 -332 (84.4) 9 -332 (84.4)	(Insert arrangement 23-35) Location Location V-axis Contact position ID (mm) X-axis Y-axis (mm) (mm) (mm) (mm) 87) + 241 (6.12) 51 + 000 (0.00) - 047 (1 96) + 154 (3.91) 52 + 000 (0.00) - 047 (1 96) + 0.15 (1.55) 53 + 000 (0.00) - 047 (1 910 - 0.61 (1.55) 53 + 000 (0.00) - 042 (1 910 - 0.61 (1.55) 55 + 000 (0.00) - 427 (1 910 - 0.61 (1.55) 56 + 008 (2.11) + 380 (8 911 - 1.42 (3.61) 56 + 0.083 (2.11) + 380 (9 911 - 3.33 (8.46) 58 + 0.083 (2.11) + 2.85 (7 91 + 3.33 (8.65) 59 + 0.083 (2.11) + 3.90 (9) .19) .661) .602) .423) 0.085) 2.07) .65) .24) .83)			ØC	
Important in the strength of t	ω	11 -332 (84) 12 -332 (84) 13 -332 (84) 14 -332 (84) 15 -332 (84) 16 -249 (6.3) 17 -249 (6.3) 18 -249 (6.3)	3) +.048 (1.22) 61 +.083 (2.11) +.000 (0 3) 047 (1.19) 62 +.083 (2.11) 095 (2) 3) 142 (3.61) 63 +.083 (2.11) 190 (4) 3) 237 (6.02) 64 +.083 (2.11) 285 (7) 3) 332 (8.43) 65 +.083 (2.11) 285 (7) 2) +.380 (9.65) 66 +.083 (2.11) 380 (9) 2) +.380 (9.65) 66 +.083 (2.11) 475 (1) 2) +.380 (9.65) 66 +.083 (2.11) 475 (1) 2) +.380 (9.65) 66 +.083 (2.11) 475 (1) 2) +.380 (9.65) 66 +.083 (2.11) 475 (1) 2) +.380 (9.63) 68 +.166 (4.22) +.333 (8) Contacts (Insert arrangement 23-35)	1.00) 1.41) 1.83) 1.24) 1.65) 1.207) 0.67)		Ē	B 40.26+0/-0.25	
No No <t< td=""><th></th><td>position ID X-axis (mm) 19 -249 (6.3 20 -249 (6.3 21 -249 (6.3 23 -249 (6.3 24 -249 (6.3 23 -249 (6.3 24 -249 (6.3 25 -166 (4.2 26 -166 (4.2</td><td>Y-axis (mm) Contact position ID 2 X-axis (mm) Y-axis (mm) 2) +.095 (2.41) 69 +.166 (4.22) +.238 (1.22) 2) +.000 (0.00) 70 +.166 (4.22) +.143 (2.2) 2) 095 (2.41) 71 +.166 (4.22) +.048 (2.2) 2) 095 (2.41) 71 +.166 (4.22) +.048 (2.2) 2) 286 (7.24) 73 +.166 (4.22) 047 (1.22) 2) 380 (9.65) 74 +.106 (4.22) 337 (2.2) 2) +.438 (10.87) 75 +.166 (4.22) 333 (2.46) 2) +.333 (8.46) 76 +.166 (4.22) 332 (2.2)</td><td>)) 3.05) 3.63) 1.22) 1.19) 3.61) 5.021 3.43) 10.85)</td><td></td><td></td><td></td></t<>		position ID X-axis (mm) 19 -249 (6.3 20 -249 (6.3 21 -249 (6.3 23 -249 (6.3 24 -249 (6.3 23 -249 (6.3 24 -249 (6.3 25 -166 (4.2 26 -166 (4.2	Y-axis (mm) Contact position ID 2 X-axis (mm) Y-axis (mm) 2) +.095 (2.41) 69 +.166 (4.22) +.238 (1.22) 2) +.000 (0.00) 70 +.166 (4.22) +.143 (2.2) 2) 095 (2.41) 71 +.166 (4.22) +.048 (2.2) 2) 095 (2.41) 71 +.166 (4.22) +.048 (2.2) 2) 286 (7.24) 73 +.166 (4.22) 047 (1.22) 2) 380 (9.65) 74 +.106 (4.22) 337 (2.2) 2) +.438 (10.87) 75 +.166 (4.22) 333 (2.46) 2) +.333 (8.46) 76 +.166 (4.22) 332 (2.2))) 3.05) 3.63) 1.22) 1.19) 3.61) 5.021 3.43) 10.85)				
Image: Constraint of the state of the s		28 -166 (4.2 29 -166 (4.2 30 -166 (4.2 31 -166 (4.2 32 -166 (4.2 33 -166 (4.2 34 -166 (4.2 35 -083 (2.1 36 -083 (2.1 37 -083 (2.1 38 -083 (2.1	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	7.24) 4.83) 2.4(1) 0.00) 2.4(1) 4.83) 7.24) 9.65) 9.46) 3.05) 3.63)			SOURIAU shall not be liable for any due to a use of the Products whi the Specifications issued by either of (professional recommendation) Country	
Image: Protect Addition Note: Protect Additin Note: Protect Addition	N	41 083 (2.1 42 083 (2.1 43 083 (2.1 44 083 (2.1 45 083 (2.1 46 +.000 (0.0	1) + 000 (0.00) 90 + 332 (8.43) - 0.47 (1) -0.95 (2.41) 91 + .332 (8.43)142 (1)190 (4.83) 92 + .332 (8.43)327 (1)285 (7.24) 93 + .332 (8.43)332 (1)380 (9.65) 94 + .428 (10.87) + .241 (1)475 (12.07) 95 + .467 (11.86) + .154 (0) +.428 (10.87) 96 + .488 (12.40) + .061 (Contacts (Insert arrangement 23-35) Location Location	1.19) 3.61) 5.02) 8.43) 5.12) 3.91)			PN: 8D723K	
Image: Interview of the stand service of the servi	_	position X-axis ID (mm) 47 +.000 (0. 48 +.000 (0. 49 +.000 (0.	Practise (mm) position ID (mm) Practise (mm) Practise (mm) 00) +333 (8.46) 97 +415 (10.54) +000 (0.0 +000 (0.0) 00) +238 (6.65) 98 +488 (12.40) -061 (1.5 -061 (1.5 00) +143 (3.63) 99 +428 (10.87) -142 (3.6 -237 (6.0)	5) 1)		ISS DATE	Latest modification - by	
NA Tolerances: ± SOURIAU WWW.SOURIAU.C		size no.	nt Number of Size Service Contact Supe				Stainless Ste	
FORMAT SOURIAU A3 8D723K3	_					NA	Tolerances:	
A3 8D723K3								
H G F E D C					_		8D723K3	
		Н	G	F	E	D	C	

