

APPLICATOR PARTS LIST

TYPE
SIDEWISE **SPLICE**
30° ANGLE APPL.

AMP INCORPORATED
HARRISBURG, PENNA.

NO.	DESCRIPTION	REQ.	PART NO.
1	■ WIRE CRIMPER	1	2-4594923
2	■ INS. CRIMPER		
3	■ ANVIL	1	1-689722-9
4	ANVIL SPACER		
5	■ SHEAR BLADE <i>FLOATING</i>	1	465324-6
6	■ REAR SHEAR PLATE	1	811239-1
7	SHEAR BLADE DEP.	1	810237
8	■ FRONT SHEAR PLATE		
9	REAR ANVIL SPACER PLT.	1	470493-7
10	FRONT ANVIL SPACER PLT.		
11	TOOL SPACER		
12	CRIMP SPACER	1	470493-4
13	FRONT STRIP GUIDE	1	465320-4
14	REAR STRIP GUIDE	1	1-465350-3
15	RAM	1	4-71167
16	TOOL HOLDER	1	465325-1
17	ADJ. CRIMP MOUNT		
18	ADJ. BLOCK		
19	APPLICATOR MOUNT ASSY.		
20	BASE PLATE	1	465317-1
21	BASE BLOCK	1	565076-1
22	STRIP GUIDE PLATE	1	692187-1
23	ANVIL HOLDER	1	811838-1
24	AUX. ANVIL HOLDER	1	811839-1
25	STRIPPER	1	811266-1
26	STRIPPER MOUNT	1	811240-1
27	RETAINER PLATE		
28	STRIPPER MOUNT BRACKET		
29	STRIPPER BUSHING		
30	STOCK DRAG	1	387650-4
31	STOCK DRAG HANDLE		
32	STOCK DRAG STUD	1	370573
33	STOCK DRAG SPRING	1	373469
34	STOCK DRAG SCREW SCREW	1	2-21006-9
35	FEED FINGER HOLDER	1	386942
36	FEED FINGER	1	386941
37	FEED FINGER TIP	1	387251
38	FEED FINGER SPACER		
39	BASE CASTING	1	570238
40	GUARD	1	461028-1
41			

NO.	DESCRIPTION	REQ.	PART NO.	
42				
43				
44				
45				
46				
47				
48				
49				
50				
51	SPRING - SHEAR	1	387083	
52				
53				
54				
55	PLATE, IDENTIFICATION	1	452373-1	
56	SCR, RH DRIVE	3	21017-6	
57				
58				
59				
60				
61	CHIP DEFLECTOR	1	455443-1	
62				
63				
64	AIR FEED ASSY	1	690021-1	
65	TENSION ADJ PLATE	1	810504	
	MISCELLANEOUS			
66				
67				
68	SCR, SHC, 3/8 x 1.75	1	3-21001-8	
69				
70				
71	MOUNT, BRACKET ASSY 30°	1	453602-1	
72	BASE, EXTENSION 30°	1	465319-2	
REV.	REVISION RECORD	DATE	BY	ECN
A	ECN 0150-1153-04	9/04	MB	16

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INC. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.

— INACTIVE —
FOR REPLACEMENT ONLY
SEE _____ FOR NEW APPLICATION

CRIMPING DATA		TERMINALS
TO APPLY TERMINAL <i>SPEC 114-2088</i>		63130
WIRE SIZE <i>(2) 040</i>	CRIMP HEIGHT	
DIA <i>±003</i>		
CORDS <i>(1 CORD)</i>	<i>088</i>	
<i>LOOPE</i>		
CRIMP	SIZE	TYPE
WIRE	<i>.120</i>	<i>0</i>
INSUL.		<i>.620</i>
SLEEVED		
INSULATION RANGE	WIRE RANGE	
EXPLODED VIEW <i>A-6022-7, -8</i>		
REMARKS: ▲ ITEM 68 MOUNTS ITEM 71 TO PRESS ▲ TENSIL STRENGTH OF CRIMP, 20 LBS MIN SPECIAL FOR PURITAN BENNETT		
■ DENOTES WEARING PARTS		
THIS APPLICATOR IS TO BE USED ON AMP-O-LECTRIC <i>1-471273-2</i> <i>AIR FEED</i>		
SERIAL NO.	DATE SHIPPED	DESIGNED
		<i>4-86</i>
CUSTOMER NAME AND ADDRESS		CHK'D BY
		<i>[Signature]</i>
APPLICATOR NUMBER	REV.	SHEET
	<i>A</i>	<i>1</i> OF <i>1</i>

THIS IS A CONTROLLED DOCUMENT.

THIS DRAWING IS UNCLASSIFIED BY AMP INCORPORATED. ALL RIGHTS RESERVED.