

Specification Sheet

Part Number: 596-00474

**PHOTOVOLTAIC SYSTEM
EQUIPPED WITH
RAPID SHUTDOWN**

Solar Label, Reflective, PHOTOVOLTAIC SYSTEM...RAPID SHUTDOWN, 5.5" x 1.75", Red, 50/pkg

Article Number	596-00474
Type	PSEWRS
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none">• Made with UV-stable inks and materials for durability and weather resistance.• Reflective properties to meet applicable NEC code requirements for reflective identification.• Supplied with an aggressive adhesive to ensure long life.• Meets NEC & IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.
Quantity Per	roll

Product Description

HellermannTyton pre-printed Solar Installation labels are designed to meet the requirements of the 2014 National Electrical Code (NEC 2014) and the 2012 International Fire Code (IFC 2012) as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

Short Description

Solar Label, Reflective, PHOTOVOLTAIC SYSTEM...RAPID SHUTDOWN, 5.5" x 1.75", Red, 50/pkg

Global Part Name

PSEWRS-242/552-RD

Technical Description

Pre-Printed Solar Label, Reflective, " PHOTOVOLTAIC SYSTEM EQUIPPED WITH RAPID SHUTDOWN", 5.5" X 1.75", Red

Local Order Number 2

Cross Reference = 10 per pack: 596-00677; Spanish version 50 per roll: 596-00823

Length L (Metric)

44.45

Width W (Imperial)

5.5

Width W (Metric)

139.7

Thickness T (Metric)

64.0

Height H (Imperial)

1.75

Height H (Metric)

44.45

Material

Type 242/552, UV Stable Reflective Vinyl w/Acrylic Laminate

Material Shortcut 242/552

Adhesive Acrylic

Halogen free No

Adhesive Operating Temperature -40°F to +302°F (-40°C to +150°C)

Operating Temperature (Metric) -40°F to +174°F (-40°C to +79°C)

Reach Complaint(Article 33) Yes

ROHS Complaint Yes

Certification/Specification WEB NEC2011 UL 969 IFC 2012 NEC2014 ANSI Standard Z535.4

Warranty (US) Yes

UL Recognized (US) Yes

Package Quantity(Imperial) 50

Package Quantity (Metric) 50

Customs Number 3919905060

Labels per Column 1

Labels per Row 1

Weight (Metric) .104

Weight (Imperial) 0.23

© 2018 HellermannTyton. All rights reserved.

[Contact Us](#) [RoHS/WEEE Compliance](#) [Disclaimer](#) [Terms and Conditions](#)