

HB-2X2-ON

~15° + 50° oval beam


TECHNICAL SPECIFICATIONS:

Dimensions	50.0 mm
Height	10 mm
Fastening	screw
Colour	clear
Box size	480 x 280 x 300 mm
Box weight	9.8 kg
Quantity in Box	800 pcs
ROHS compliant	yes ⓘ















MATERIAL SPECIFICATIONS:

Component	Type	Material	Colour
HB-2X2-ON	Lens array	PMMA	clear





PHOTOMETRIC DATA (MEASURED):

<p></p> <p>LED QUICK FLUX XTP 2x4 xxx LS G5 FWHM 16.0 + 55.0° Efficiency 93 % Peak intensity 2.300 cd/lm Required components:</p>		
<p></p> <p>LED XD16 FWHM 13.0 + 55.0° Efficiency 89 % Peak intensity 2.400 cd/lm Required components:</p>		
<p></p> <p>LED XD16 2x2 cluster FWHM 27.0 + 49.0° Efficiency 90 % Peak intensity 1.400 cd/lm Required components:</p>		
<p></p> <p>LED XP-G2 FWHM 14.0 + 55.0° Efficiency 89 % Peak intensity 2.670 cd/lm Required components:</p>		



PHOTOMETRIC DATA (MEASURED):





LED XP-L HI
 FWHM 14.0 + 55.0°
 Efficiency 91 %
 Peak intensity 2.600 cd/lm
 Required components:





LED LUXEON V
 FWHM 22.0 + 51.0°
 Efficiency 92 %
 Peak intensity 1.800 cd/lm
 Required components:








LED PrevaLED Brick DC 2x8
 FWHM 15.0 + 54.0°
 Efficiency 91 %
 Peak intensity 2.600 cd/lm
 Required components:



LED Oslon Square Gen3
 FWHM 15.0 + 54.0°
 Efficiency 91 %
 Peak intensity 2.600 cd/lm
 Required components:




PHOTOMETRIC DATA (MEASURED):

<p> SEOUL SEMICONDUCTOR</p> <p>LED Z8Y22 FWHM 20.0 + 53.0° Efficiency 91 % Peak intensity 1.600 cd/lm Required components:</p>		
<p>TRIDONIC</p> <p>LED RLE G2 HP 2x8 4000lm FWHM 15.0 + 55.0° Efficiency 94 % Peak intensity 2.500 cd/lm Required components:</p>		

PHOTOMETRIC DATA (SIMULATED):




LED XHP35 HI
FWHM 16.0 + 50.0°
Efficiency 90 %
Peak intensity 0.000 cd/lm
Required components:




LED XP-E2
FWHM 10.0 + 50.0°
Efficiency 90 %
Peak intensity 0.000 cd/lm
Required components:



LED XP-G3
FWHM 17.0 + 48.0°
Efficiency 89 %
Peak intensity 0.000 cd/lm
Required components:




LED XP-L
FWHM 18.0 + 50.0°
Efficiency 88 %
Peak intensity 0.000 cd/lm
Required components:




PHOTOMETRIC DATA (SIMULATED):




LED XT-E
 FWHM 14.0 + 55.0°
 Efficiency 91 %
 Peak intensity 2.900 cd/lm
 Required components:




LED LUXEON 5050
 FWHM 23.0 + 51.0°
 Efficiency 89 %
 Peak intensity 1.700 cd/lm
 Required components:



LED LUXEON C
 FWHM 12.0 + 54.0°
 Efficiency 91 %
 Peak intensity 3.400 cd/lm
 Required components:




LED LUXEON TX
 FWHM 14.0 + 50.0°
 Efficiency 90 %
 Peak intensity 0.000 cd/lm
 Required components:



PHOTOMETRIC DATA (SIMULATED):

OSRAM
Opto Semiconductors

LED Duris S8
FWHM 26.0 + 49.0°
Efficiency 88 %
Peak intensity 1.590 cd/lm
Required components:



GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)