



注記
NOTES

1. 適合ハウジング アッセンブリ; 52266-***|*
APPLICABLE HS'G ASS'Y; 52266-***|*
2. 嵌合相手; 50148-8*00
MATES WITH; 50148-8*00

50147-8100	バラ状 LOOSE
50147-8000	連鎖状 CHAIN
MATERIAL NO.	端子形状 FORM

材料 MATERIAL	リン青銅 錫メッキ (+0.2) PHOSPHOR BRONZE TIN PLATING (+0.2)
適用電線範囲 WIRE RANGE	AVSS-0.3/0.3F AVSS-0.5/0.5F CAVS-0.3 CAVS-0.5 ISO-0.5 AWG #22/#20
被覆外径 INS. RANGE	φ1.4-1.9

REVISED EC NO: JTR2012-0084 DRWNG:SANDO 2012/02/29 CHKD:SANDO 2012/03/02 APPR:MAVAMOTO 2012/03/16 C1	GENERAL TOLERANCES (UNLESS SPECIFIED)
	10 UNDER ±0.2
	10 OVER 30 UNDER ±0.25
	30 OVER ±0.3
ANGULAR ±3 °	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE MM ONLY	
DRAWN BY M. SANO	DATE 1991/7/17
CHECKED BY M. SAKANO	DATE 1992/8/6
APPROVED BY MENOMOTO	DATE 1992/8/6
MATERIAL NO.	
SEE CHART	
SIZE A3	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION

SCALE 10:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION	TITLE 2.5 MINI WATERPROOF CONN.CRIMP PIN.
MOLEX MOLEX INCORPORATED		DOCUMENT NO. SD-50147-001	SHEET NO. 1 OF 1