

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION  
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISONS					
J	-	P	LTR	DESCRIPTION	DATE	DWN	APVD
		G3	REVISED	ECR-15-010703	21JUL15	KF	RK

〈MOUNTING DIMENSIONS FOR P. C. BOARD; TOLERANCE ±0.1〉  
 プリント基板取付寸法図

一般公差: ±0.1  
 (公差は累積しないこと)

1. MUST BE KEPT BETWEEN [X] AND 2  
 2. THE MATING PLUG HSG. PART NUMBER: 174514, 174515, 917981, 917989  
 3. RECOMMENDED MOUNTING SCREW: 3mm DIA, 6mm LENGTH (MAX.)  
 PAN HEAD, CLASS 2 TAPPING SCREW SPECIFIED IN JIS B1115, B1122  
 (TIGHTENING TORQUE: 0.4N-m (4Kg-cm) MAX)  
 4. APPLICABLE PRODUCT SPEC NO.: 108-5280, 108-5342  
 5. CIRCUIT NUMBER  
 POWER CIRCUIT NO. ③③ ~ ③⑧  
 SIGNAL CIRCUIT NO. ① ~ ③②  
 6. MARKING FOR DISCERNMENT OF THE CONTACT FINISH

1. [X] 面から2mmの範囲で測定  
 2. 嵌合相手ハウジング型: 174514, 174515, 917981, 917989  
 3. 推奨取付ねじ: JIS B1115, B1122 タッピングねじ, なべ2種  
 呼び径3, 長さ6mm以下 (締付けトルク: 0.4N-m (4kg-cm) 以下)  
 4. 適用製品規格番号: 108-5280, 108-5342  
 5. 回路番号: 上図参照のこと  
 パワー回路 ③③ ~ ③⑧  
 シグナル回路 ① ~ ③②  
 6. コンタクト仕上識別マーク

52	SELECTIVE-TIN (MATTE)	SELECTIVE GOLD (部分金めっき) × 10 PRE-TINNED (錫めっき) × 28	---	① ② ⑥ ⑦ ⑨ ⑩ ⑪ ⑭ ⑮ ⑯	YELLOW 黄色	2-5175521-7
3	TIN-LEAD	SELECTIVE GOLD (部分金めっき) × 3 PRE-TINNED (錫めっき) × 35	---	① ② ⑩	GRAY 灰色	3-175521-6
2	TIN-LEAD	SELECTIVE GOLD (部分金めっき) × 10 PRE-TINNED (錫めっき) × 28	---	① ② ⑥ ⑦ ⑨ ⑩ ⑪ ⑭ ⑮ ⑯	YELLOW 黄色	2-175521-7
0		PRE-TINNED 錫メッキ × 38	---	---	YELLOW 黄色	175521-7
0		PRE-TINNED 錫メッキ × 38	---	---	GRAY 灰色	175521-6
MARKING	SOLDERING SIDE 半田付け部	CONTACT SIDE 接触部側	POWER CIRCUIT NO. パワー回路	SIGNAL CIRCUIT NO. シグナル回路	HOUSING COLOR ハウジング色	PART NO
	FINISH OF CONTACT タブ仕上 (本数)		CIRCUIT NO. OF GOLD PLATED CONTACT 金メッキ端子使用回路番号			

THIS DRAWING IS A CONTROLLED DOCUMENT.

DWN	T. SHINOHARA	11JUL11
CHK	K. BETSUI	11JUL11
APVD	K. BETSUI	11JUL11

TE Connectivity

38POSITION CAP HOUSING ASSEMBLY  
 040/070 SERIES HYBRID I/O CONNECTOR

SIZE	CAGE CODE	DRAWING NO	RESTRICTED TO
A2	00779	C=175521	-

SCALE 2:1 SHEET 1 OF 1 REV G3

1471-9 (3/11)

175521

A