

## Label - EML (50X10)R - 0830483

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Label, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, Mounting type: Adhesive, Lettering field: 50 x 10 mm

The figure shows a version of the article

### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Weight per Piece (excluding packing) | 480.0 g  |
| Custom tariff number                 | 39199000 |
| Country of origin                    | Germany  |

### Technical data

#### Dimensions

|            |       |
|------------|-------|
| Length (b) | 50 mm |
| Width (a)  | 11 mm |

#### Ambient conditions

|                                 |   |
|---------------------------------|---|
| Ambient temperature (operation) | -40 °C ... 150 °C   |
| Ambient temperature (assembly)  | > 5 °C  |
| Recommended storage conditions  | 21 °C / 50% relative humidity. Storage in poly bags is recommended prior to processing. |

#### General

|                                     |                                |
|-------------------------------------|--------------------------------|
| Color                               | white                          |
| Components                          | free from silicone and halogen |
| Material                            | Polyester                      |
| Wipe resistance                     | DIN EN 61010-1 (VDE 0411-1)    |
| Number of individual labels         | 2500                           |
| Number of individual labels per row | 1                              |
| RoHS compliant                      | Yes                            |
| Adhesive                            | Acrylic                        |

# Label - EML (50X10)R - 0830483

## Technical data

### General

|   |                                     |
|---|-------------------------------------|
| File number   | UL-MH48542 / PC-010 (white foil)    |
| Printability  | Thermal transfer                    |
| Device  | 5146477 THERMOMARK ROLL             |
|   | 5146723 THERMOMARK ROLL X1          |
|   | 5146231 THERMOMARK X1.2             |
| Ink ribbon  | 5145384 THERMOMARK-RIBBON 110       |
|   | 0829544 THERMOMARK-RIBBON 110 BU    |
|   | 0829542 THERMOMARK-RIBBON 110 GN    |
|   | 0829543 THERMOMARK-RIBBON 110 RD    |
| Test for substances that would hinder coating with paint or varnish | VW PV 3.10.7:2005-02                |
| Result  | Test passed                         |
| Test specification weathering-resistance                            | Following ISO 4892-2:2013-03        |
| Test duration   | 96 h                                |
| Wipe resistance test result   | Test passed                         |
| Salt spray test specification                                       | DIN EN 60068-2-11:2000-02           |
| Test duration   | 96 h                                |
| Salt spray testing result   | Test passed                         |
| Alternating condensation climate with SO2 test specification        | following DIN 50018:2013-05         |
| Climate level   | AHT 1.0 S                           |
| Cycles  | 2                                   |
| Condensation test result  | Test passed                         |
| Wipe resistance of test specification inscriptions                  | DIN EN 61010-1 (VDE 0411-1):2011-07 |
| Result  | Test passed                         |
| Foil strength   | 50 µm                               |
| Adhesive strength   | 20 µm                               |
| Marking mounting type   | Adhesive                            |

### Standards and Regulations

|                                  |                             |
|----------------------------------|-----------------------------|
| Connection in acc. with standard | UL                          |
| Wipe resistance                  | DIN EN 61010-1 (VDE 0411-1) |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 24190219 |
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.0 | 27141137 |
| eCl@ss 5.1 | 27141137 |

## Label - EML (50X10)R - 0830483

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 6.0 | 27141137 |
| eCl@ss 7.0 | 27141137 |
| eCl@ss 8.0 | 27149129 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC000761 |
| ETIM 4.0 | EC000761 |
| ETIM 5.0 | EC001288 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |

### Approvals

#### Approvals

---

#### Approvals

UL Recognized

---

#### Ex Approvals

---

Approvals submitted

---

#### Approval details

|   |
|---|
| UL Recognized  |
|---|