

## Panel feed-through - SACC-DSI-M12FS-5CON-PG9/0,5 P - 1436356

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



Sensor/Actuator flush-type connector, socket, 5-pos., M12, A-coded, rear/screw mounting with Pg9 thread, with 0.5 m TPE litz wire, 5 x 0.25 mm<sup>2</sup>, plastic version



### Key commercial data

|                      |   |
|----------------------|---|
| Packing unit         | 1 PCE   |
| Catalog page         | Page 61 (PC-2011)   |
| GTIN                 | <br>4 046356 438322 |
| Custom tariff number | 85444290  |
| Country of origin    | GERMANY   |

### Technical data

#### General data

|                                 |                                  |
|---------------------------------|----------------------------------|
| Rated current at 40°C           | 4 A                              |
| Rated voltage                   | 60 V                             |
| Number of positions             | 5                                |
| Volume resistance               | ≤ 3 mΩ                           |
| Insulation resistance           | ≥ 100 MΩ                         |
| Length of cable                 | 0.5 m                            |
| Ambient temperature (operation) | -25 °C ... 85 °C (Plug / socket) |

#### General characteristics

|                        |                                       |
|------------------------|---------------------------------------|
| Standards/regulations  | M12 plug-in connector IEC 61076-2-101 |
| Coding                 | A - standard                          |
| Surge voltage category | II                                    |
| Pollution degree       | 3                                     |
| Degree of protection   | IP67                                  |

# Panel feed-through - SACC-DSI-M12FS-5CON-PG9/0,5 P - 1436356

## Technical data

### General characteristics

|                          |                                 |
|--------------------------|---------------------------------|
| Contact material         | CuZn                            |
| Contact surface material | Au                              |
| Contact carrier material | PA 66                           |
| Material, knurls         | PA 66                           |
| Sealing material         | Viton                           |
| Mounting type            | Rear mounting Pg9 With flat nut |
| Connection method        | Individual wires                |
| Status display           | No                              |

### Conductor data

|                                    |  |
|------------------------------------|--|
| Cable type                         | TPE litz wire                                |
| Conductor cross section            | 0.25 mm <sup>2</sup>                         |
| AWG signal line                    | 24   |
| Conductor structure signal line    | 14x 0.15 mm                                  |
| Core diameter including insulation | 1.15 mm ±0.07 mm                             |
| Thickness, insulation              | 0.21 mm                                      |
| Wire colors                        | Black, brown, blue, white, gray              |
| Material conductor insulation      | TPE  |
| Conductor material                 | Tin-plated Cu litz wires                     |
| Insulation resistance              | ≥ 20 MΩ*km                                   |
| Conductor resistance               | ≤ 80 Ω/km                                    |
| Nominal voltage, conductor         | 300 V  |
| Test voltage, conductor            | 2000 V AC                                    |
| Ambient temperature (operation)    | -25 °C ... 85 °C (cable, fixed installation) |

## Classifications

### ETIM

|          |          |
|----------|----------|
| ETIM 3.0 | EC002062 |
| ETIM 4.0 | EC002061 |
| ETIM 5.0 | EC002061 |

### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 11     | 31251501 |
| UNSPSC 12.01  | 31251501 |
| UNSPSC 13.2   | 31251501 |
| UNSPSC 6.01   | 31251501 |
| UNSPSC 7.0901 | 31251501 |

# Panel feed-through - SACC-DSI-M12FS-5CON-PG9/0,5 P - 1436356

## Classifications

eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.0 | 27250313 |
| eCl@ss 4.1 | 27250313 |
| eCl@ss 5.0 | 27143423 |
| eCl@ss 5.1 | 27143423 |
| eCl@ss 6.0 | 27143423 |
| eCl@ss 7.0 | 27449001 |

## Approvals

Approvals

---

Approvals

GOST

---

Ex Approvals

---

Approvals submitted


---

Approval details




## Drawings

Dimensioned drawing



Schematic diagram




Pin assignment M12 socket, 5-pos., A-coded, socket side view

Housing cutout for M12 fastening thread, mounting panel with feed-through hole (alternative with surface as protection against rotation)

## Panel feed-through - SACC-DSI-M12FS-5CON-PG9/0,5 P - 1436356

Dimensioned drawing



Circuit diagram



Contact assignment of the M12 socket

M12 flush-type connector