



# HDMI CONNECTOR SCREW TYPE

- NOTE:
- 1.MATERIAL : BRASS C2680-1/2H(HV120~140),T=0.2±0.02mm.  
TERMINAL : BRASS C2680-EH(HV160~175),T=0.5±0.02mm.  
SHELL : BRASS C2680-EH(HV160~175),T=0.5±0.02mm.
  - 2.PLATING : LCP(E130I)+30%G.F.(UL94-0),BLACK.
  - TERMINAL : AU PLATED ON CONTACT AREA (SEE ORDER INFORMATION),  
100u" Sn PLATED ON SOLDER TAIL AREA,  
BOTH OVER 50u" MIN. Ni UNDERPLATED OVERALL.
  - 3.MECHANICAL CHARACTERISTICS :  
SHELL : 100u"MIN. WELDABLE Ni OVERALL.  
INSERTION FORCE : 4.5kgf MAX.  
WITHDRAWING FORCE : 1kgf ~ 4kgf.
  - 4.CRITICAL DIM QUANTITY: 0 ; MAJOR DIM QUANTITY: 4.

14/01/17	Jody		NEW DWG		AO
DATE	DR.BY	ECN.NO.	DESCRIPTION	MARK	VER.

Cnc Tech, LLC

UNLESS OTHERWISE SPECIFIED			TITLE: HDMI A Type Female 19P SMT with Screw Hole & 4 DIP Tails, G/F, Black
----------------------------	--	--	---

-TOLERANCES-					
X.X	±0.38	X.X°	±2°	APPD:	PRODUCT NO: 2000-1-2-23-00-BK
X.XX	±0.25	X.XX°	±1°	CHECK:	DATE
X.XXX	±0.13	X.XXX°	±0.5°	DRAW:	SCALE
					UNIT
					TYPE
					PAGE
					1/1