


FCI P/N

10121130-P0011YYLF



P1

P2

110±2

COLOR STRIP

WIRE SCHEME

P1	P2
1	1
2	2
3	3
...	...
12	12

NOTES:

1. TEST:

□/S:100% TEST.
 CONNECTION RESISTANCE: 2 Ωhm MAX.
 HI-POT:300V/10mS.
 INSULATION RESISTANCE: 10M Ωhm MIN.

2. ROHS COMPLIANCE

②	MINITEK IDC CONN.	Minitex 2x6 position IDC receptacle, 0.76um gold, with central key and friction latch bump	2	PC
①	FLAT CABLE	Flat cable UL2651, 28AWGx12C, Pitch1.0, Grey PVC	A/R	M
No.	NAME	DESCRIPTION	QTY	UNIT
www.fciconnect.com		surface - ✓ tolerance std - - projection	mm	
		TOLERANCES UNLESS OTHERWISE SPECIFIED		
Dr	Tom Feng	2012-11-16	ANGULAR	LINEAR
Eng	Tom Feng	2012-11-16	0.X	±-
Chr	Roger Cheng	2012-11-16	0.XX	±-
Appr	Jackson Wang	2012-11-16	0.XXX	±-
Product family		size A3 Scale 2:3		
Product family		ECN		
Product family		Spec ref -		
title Minitex IDC Cable Ass'y		dwg no 10121130		Rev. A
catalog no -		CUSTOMER		sheet 1 of 1

rev	ecn no	dr	date
A	-	TF	2012-11-16



Copyright FCI.