

# NT24k<sup>®</sup> Modular Industrial Switch

N-Tron<sup>®</sup> Networking Series



## Managed Gigabit Industrial Ethernet Switch

The N-Tron<sup>®</sup> series NT24k<sup>®</sup> is a modular managed switch designed for factory automation, utilities, SCADA, security surveillance and other industrial applications.



The Red Lion N-Tron series NT24k managed industrial Ethernet switch features connectivity for up to 24 Gigabit ports and offers a wide range of connectivity options—including 100Base, Gigabit, fiber optic and copper options—in a rugged 1U 19" rackmount enclosure. Designed to handle the most demanding environments, the NT24k delivers wire-speed throughput and includes dual power inputs, expanded shock and vibration tolerances, extreme operating temperature range and three slots to accommodate mix-and-match port modules. N-Ring<sup>™</sup> technology restores network communication within ~30ms of fault detection. Robust remote monitoring capabilities make management easy.

### APPLICATIONS

- > Factory Automation
- > Utilities
- > SCADA
- > Security Surveillance
- > Transportation
- > Alternative Energy

### PRODUCT HIGHLIGHTS

- > All Gigabit Modular Design
- > Up to 24 Port Connections
- > High Environmental Specifications
- > N-Ring Advanced Ring Technology
- > Robust Remote Monitoring
- > Smart Plug-and-Play Operation

### FEATURES & BENEFITS

- > Supports up to three of the following port modules:
  - 8-port 10/100/1000BaseT(X) module
  - 8-port 100Base fiber module
  - 8-port 1000Base fiber module
  - 8-port Gigabit SFP module
  - 8-port dual mode SFP module (100Base or 1000Base SFP transceivers)
- > -40°C to 85°C operating temperature
- > Dual power input options:
  - Low Voltage: 18-49 VDC
  - High Voltage: 90-264 VAC or 90-300 VDC
- > Onboard temperature sensor
- > ESD and surge protection diodes on all copper ports
- > Auto-sensing 10/100/1000BaseT(X), duplex and MDIX
- > USB configuration port
- > Configurable alarm contact
- > Optional backup/restore configuration device
- > Fully managed features include:
  - Jumbo frame support
  - SNMP v1, v2, v3
  - Web browser management
  - Detailed ring map and fault location charting
  - RSTP - 802.1d, 802.1w, 802.1D
  - Trunking and port mirroring
  - 802.1Q tag VLAN and port VLAN
  - IEEE 802.1x with RADIUS remote server authentication
  - 802.1p QoS, port QoS and DSCP
  - DHCP client
  - Event Log
  - SNTP (Simple Network Time Protocol)
  - Multi-Member N-Ring<sup>™</sup> technology with ~30ms healing
  - N-Link<sup>™</sup> redundant ring technology
  - N-View<sup>™</sup> monitoring technology
  - EtherNet/IP<sup>™</sup> CIP<sup>™</sup> messaging

industrial  
networking



EtherNet/IP<sup>™</sup>

# Managed Gigabit Industrial Ethernet Switch Specifications

## SWITCH PROPERTIES

Number of MAC Addresses: 16K  
 Aging Time: Programmable  
 Latency (typical): 1.6 µs  
 Switching Method: Store & Forward  
 MTBF: >1 million hours

## POWER INPUT

Input Voltages:  
 Low Voltage: 18-49 VDC  
 High Voltage: 90-264 VAC or 90-300 VDC  
 Input Current (max): 2.26A @ 24VDC  
 Input Current (max): 790mA @120 VAC/450mA @ 124VDC  
 BTU/hr: 185 @ 24VDC  
 BTU/hr: 365 @ 120VAC/190 @ 124VDC

## CONNECTORS

10/100/1000BaseT(X): Up to 24 RJ45 copper ports  
 100BaseFX: Up to 24 SC or ST fiber ports  
 1000BaseFX: Up to 24 SC fiber ports  
 100BaseSX/LX SFP: Up to 24 LC fiber ports  
 1000BaseGX SFP: Up to 24 LC fiber ports

## RELIABILITY

MTBF: >1 million hours

## NETWORK MEDIA

10BaseT: ≥Cat3 cable  
 100BaseTX: ≥Cat5 cable  
 1000BaseT: ≥Cat5 cable  
 100BaseFX, 1000BaseSX Multimode: 50-62.5/125µm  
 100BaseFX, 1000BaseLX Singlemode: 7-10/125µm

## RECOMMENDED WIRING CLEARANCE

Front and Back: 4" (10.2 cm)

## CERTIFICATION & COMPLIANCE

Product Safety:  
 ANSI/ISA 12.12.01-2013 Class I and II, Div. 2 and Class III, Div. 1 and 2, Groups A, B, C and D Hazardous Locations  
 UL508 Industrial Control Equipment  
 CAN/CSA-C22.2 No. 213-M1987 Class I Div. 2 Hazardous Locations  
 CAN/CSA-C22.2 No. 14-M1987 Industrial Control Equipment  
 Emissions:  
 FCC Title 47, Part 15, Radio Frequency Devices, Subpart B ANSI C63.4-2009; Industry Canada ICES-003, EN 55011; EN 61000-6-4, EN 61000-3-2, EN61000-3-3, EN 55032  
 Immunity:  
 EN 55024, EN 61000-6-2; IEC 61000-4-2 (ESD); IEC 61000-4-3 (RFAM); IEC 61000-4-4 (EFT); IEC 61000-4-5 (SURGE); IEC 61000-4-6 (RFCM); IEC 61000-4-8 (PFMF); IEC 61000-4-11 (VDI)  
 Other:  
 ABS Type Approval for Shipboard Applications; EMC Directive 2014/30/EU; LV Directive 2014/35/EU GOST-R, RoHS Compliant


## ENVIRONMENTAL

Operating Temperature: -40° C to 85° C  
 Operating Humidity: 5% to 95% (Non Condensing)  
 Operating Altitude: 0 to 10,000 ft.  
 Shock: 50g @ 10ms  
 Vibration/Seismic: 30g, 10-200 Hz, triaxial

## MECHANICAL

Case Dimensions  
 Height: 1.9" (4.8 cm)  
 Width: 17.5" (44.5 cm)  
 Depth: 12.7" (32.0 cm)  
 Weight (maximum): 12.85 lbs (5.83 kg)  
 Mount: Rackmount 1U

## DIMENSIONS



All specifications are subject to change. Consult the company website for more information.

# Managed Gigabit Industrial Ethernet Switch Specifications

## NT24K-FX8 MODULE - 100 MB FIBER TRANSCEIVER CHARACTERISTICS

Fiber Mode	MM	SM	SM	SM
Fiber Length*	2km	15km	40km	80km
TX Power Min	-19 dBm	-15 dBm	-5 dBm	-5 dBm
RX Sensitivity Max	-31 dBm	-31 dBm	-34 dBm	-34 dBm
Wavelength	1310 nm	1310 nm	1310 nm	1550 nm

## NT24K-GX8 MODULE - GIGABIT FIBER TRANSCEIVER CHARACTERISTICS

Fiber Mode	MM	SM	SM	SM
Fiber Length*	550m @ 50/125µm 300m @ 62.5/125µm	10km	40km	80km
TX Power Min	-9.5 dBm	-9.5 dBm	-5 dBm	0 dBm
RX Sensitivity Max	-17 dBm	-20 dBm	-23 dBm	-24 dBm
Wavelength	850 nm	1310 nm	1310 nm	1550 nm
Laser Type	VCSEL	FP	DFB	DFB

## NT24K-SFP-DM8 MODULE - SFP 100BASE FIBER TRANSCEIVER CHARACTERISTICS

Fiber Mode	MM	SM	SM	SM
Fiber Length*	2km	15km	40km	80km
TX Power Min	-19 dBm	-15 dBm	-5 dBm	-5 dBm
RX Sensitivity Max	-31 dBm	-34 dBm	-34 dBm	-34 dBm
Wavelength	1310 nm	1310 nm	1310 nm	1550 nm
Laser Type	FP	FP	FP	DFB

## NT24K-SFP-DM8 OR NT24K-SFP8 MODULES- SFP GIGABIT FIBER TRANSCEIVER CHARACTERISTICS

Fiber Mode	MM	SM	SM	SM
Fiber Length*	550m @ 50/125µm 275m @ 62.5/125µm	10km	40km	80km
TX Power Min	-9.5 dBm	-9.5 dBm	-2 dBm	0 dBm
RX Sensitivity Max	-17 dBm	-20 dBm	-22 dBm	-24 dBm
Wavelength	850 nm	1310 nm	1310 nm	1550 nm
Laser Type	VCSEL	FP	DFB	DFB

\* Fiber Length distances represent typical performance.  
Link budgets should be evaluated based on specific application conditions.

## ORDERING GUIDE

PART NUMBER	DESCRIPTION
NT24K-DC1	1U rackmount 3-slot modular Gigabit switch with one redundant 18-49 VDC power input
NT24K-DC2	1U rackmount 3-slot modular Gigabit switch with two redundant 18-49 VDC power inputs
NT24K-AC1	1U rackmount 3-slot modular Gigabit switch with one 90-264 VAC/90-300 VDC power input
NT24K-AC2	1U rackmount 3-slot modular Gigabit switch with two 90-264 VAC/90-300 VDC power input
NT24K-AC1-DC1	1U rackmount 3-slot modular Gigabit switch with one each 90-264 VAC/90-300 VDC and 18-49 VDC power inputs
NT24K-FP	Filler panel (required to fill vacant module slots)
NT24-PMK	Panel mount kit
NTCD-CFG	Configuration recovery device
NTPC-AC-US	AC power cord
NTPS-24-3	DIN rail power supply 3.0 Amp@24 VDC

PORT MODULES & TRANSCEIVERS	
NT24K-TX8	8-port 10/100/1000BaseT module
NT24K-FX8-XX	Slide-in module with 8 100BaseFX multimode fiber ports, 2km (SC or ST)
NT24K-FXE8-XX-YY	Slide-in module with 8 100BaseFX singlemode fiber ports (SC or ST)
NT24K-GX8-SC	Slide-in module with 8 1000BaseFX multimode fiber ports, 550m (SC)
NT24K-GXE8-SC-ZZ	Slide-in module with 8 1000BaseFX singlemode fiber ports (SC)
NT24K-SFP8	Slide-in module with 8 SFP expansion slots; supports 1000Base SFP transceivers*
NT24K-SFP-DM8	Slide-in module with 8 dual mode SFP expansion slots; supports 100Base or 1000Base SFP transceivers*
NTSFP-FX	100BaseFX multimode fiber SFP pluggable mini-GBIC transceiver (LC style connector, 2km)**
NTSFP-FXE-YY	100BaseFX singlemode fiber SFP pluggable mini-GBIC transceiver (LC style connector)**
NTSFP-TX	1000BaseT copper SFP pluggable mini-GBIC transceiver
NTSFP-SX	1000BaseSX multimode fiber SFP pluggable mini-GBIC transceiver
NTSFP-LX-ZZ	1000BaseLX singlemode fiber SFP pluggable mini-GBIC transceiver

Where: XX = ST or SC connector (ST not available on some GX modules); YY = 15, 40, or 80 for FX singlemode, blank for multimode; ZZ = 10, 40, or 80 for GX singlemode. \*SFP transceivers sold separately. \*\*For use with SFP DM8 module only



[www.redlion.net](http://www.redlion.net)

Connect. Monitor. Control.

**Americas**  
sales@redlion.net

**Asia-Pacific**  
asia@redlion.net

**Europe  
Middle East  
Africa**  
europe@redlion.net

+1 (717) 767-6511

As the global experts in communication, monitoring and control for industrial automation and networking, Red Lion has been delivering innovative solutions for over forty years. Our automation, Ethernet and cellular M2M technology enables companies worldwide to gain real-time data visibility that drives productivity. Product brands include Red Lion, N-Tron and Sixnet. With headquarters in York, Pennsylvania, the company has offices across the Americas, Asia-Pacific and Europe. Red Lion is part of Spectris plc, the productivity-enhancing instrumentation and controls company. For more information, please visit [www.redlion.net](http://www.redlion.net).

ADLD0331 051816 © 2016 Red Lion Controls, Inc. All rights reserved. Red Lion, the Red Lion logo, N-Tron and Sixnet are registered trademarks of Red Lion Controls, Inc. All other company and product names are trademarks of their respective owners.