



Innovative **Technology**
for a **Connected** World

RD2458-5-OTDR

Tri-Band Omnidirectional Outdoor Antenna



TRI-BAND 2400/5300/5800 MHz OPERATION OUTDOOR ANTENNA

Laird Technologies' Tri-Band RD2458-5-OTDR series antennas are high-gain (3 dB @ 2.4 GHz and 5 dBi @ 5 GHz) omnidirectional antennas designed for outdoor use. They are rugged and reliable. The antenna features a 360° horizontal transmission pattern and a 90° vertical transmission pattern.

FEATURES

- Tri-Band operation: 2.4 GHz, 5.3 GHz, 5.8 GHz
- Extends range of wireless access points or wireless bridges
- N male connector
- IP-67 seal rating

MARKETS

- 2.5, 5.3 GHz Wireless Access Points
- 2.5, 5.3 GHz Wireless Client Bridges
- 2.5, 5.3 GHz Wireless Routers
- Public safety wireless systems
- 802.11a/b/g wireless equipment
- WiMAX

global solutions: local support.™


Americas: +1.847.839.6907
IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12
IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022
IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANTENNA PATTERNS



Freq (MHz)	peak (dBi)	Angle (o)	Avg (dBi)
2400.00	1.63	58.12	-2.24
2450.00	3.26	63.75	-1.75
2500.00	1.57	68.12	-2.33
5150.00	5.36	77.50	-0.63
5250.00	2.96	81.25	-1.93
5350.00	4.24	83.12	-1.05
5725.00	3.83	39.37	-0.57
5850.00	2.59	315.00	-2.10

SPECIFICATIONS

Part Number:	RD2458-5-OTDR
Frequency GHz:	2.4-2.5, 5.15-5.35, 5.725-5.85 MHz
Gain:	2.0 dBi @2 GHz, 4.0 dBi @5 GHz
3 dB Beamwidth-Azimuth:	Omnidirectional
3 dB Beamwidth-Elevation:	90°
Polarization:	Linear Vertical
VSWR:	2.0:1
RF Connector:	N (m) Reverse TNC
Power Rating:	10 W
Impedance:	50 Ohm
Dimensions:	7.6 x .05 in (193 x 12.7 mm)
Weight:	45.4 g
Operational Temperature:	-10°C to +70°C
Mount Style:	Direct
Seal Rating:	IP-67
RoHS:	Compliant

SYSTEM ORDERING INFORMATION

RD2458-5-OTDR-NM TriBand 2.4/5.3/5.8 GHz Omnidirectional – N male connector

NOTES

- All shipments F.O.B. Schaumburg, IL 60173

ANT-DS-RD2458-5-OTDR 1012

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies makes no warranties as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2012 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.