

## Specification Sheet

Part Number: 155-32602



Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.75-5.0mm/ PA66HIRHS; Black; 500/Pack

<b>Article Number</b>	155-32602
<b>Type</b>	FT6LG.M.St.Aufn.II
<b>Color</b>	Black (BK)
<b>Features &amp; Benefits</b>	<ul style="list-style-type: none"><li>•Head design contains clamping rails to provide full circumferential compression around bundles.</li><li>•Bent tail allows for quick insertion into head.</li></ul>
<b>Quantity Per</b>	bag
<b>Product Description</b>	Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.
<b>Short Description</b>	Connector Clip; Hole Dia. 6.5-7.0mm; Panel 0.75-5.0mm/ PA66HIRHS; Black; 500/Pack

Global Part Name

FT6LG.M.St.Aufn.II-PA66HIRHS-BK

Fixation Method

Fir Tree

Panel Thickness Min(Imperial)

0.03

Panel Thickness Max(Imperial)

0.2

Panel Thickness Min (Metric)

0.75

Panel Thickness Max (Metric)

5.0

Mounting Hole Diameter D (Imperial)

0.26 - 0.28

Mounting Hole Diameter D (Metric)

6.5 - 7.0 mm

Mounting Hole Diameter D Min (Imperial)

0.26

Mounting Hole Diameter D Max (Imperial)

0.28

Mounting Hole Diameter D Max (Metric)

7.0

Disc Diameter(Metric)

16

Disc Diameter (Imperial)

0.63

Material

Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS)

Material Shortcut

PA66HIRHS

<b>Flammability</b>	UL 94 HB
<b>Operating Temperature (Metric)</b>	-40°F to +221°F (-40°C to +105°C)
<b>Reach Complaint(Article 33)</b>	Yes
<b>ROHS Complaint</b>	Yes
<b>Package Quantity(Imperial)</b>	500
<b>Package Quantity (Metric)</b>	500
<b>Customs Number</b>	3926909987
<b>Content Unit(BMEcat)</b>	pcs.
<b>Weight (Metric)</b>	0.8