

## Axial Leaded Ceramic Capacitors

## UP025SL1R8D-A-BZ



## ■ Features

- Item Summary  
1.8pF±0.5pF, 50V,  
SL,  $\phi$  2.0x2.3mm
- Lifecycle Stage  
Non-preferred
- Standard packaging quantity (minimum)  
Taping 5000pcs

## ■ Products characteristics table

Capacitance	1.8 pF $\pm$ 0.5pF
Case Size (mm)	2.0x2.3
Rated Voltage	50 V
Q (min)	436 at 1MHz
Temperature Characteristic (JIS)	SL
Operating Temp. Range (JIS)	-25 to +85 °C
Temperature Characteristic	+350 to -1000 ppm/°C
Insulation Resistance (min)	10 G $\Omega$
RoHS2 Compliance (10 subst.)	Yes
REACH Compliance (173 subst.)	Yes
Soldering	Wave

## ■ External Dimensions

Dimension D	Max $\phi$ 2.0 mm
Dimension L	Max 2.3 mm
Dimension d	$\phi$ 0.45 $\pm$ 0.05 mm

2017.04.30

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.  
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.  
 Before making final selection, please check product specification.