








APPLICABLE STANDARD						
RATING	OPERATING TEMPERATURE RANGE	-40°C TO + 85°C (NOTE 1) 			STORAGE TEMPERATURE RANGE	-10°C TO + 60°C
	OPERATING HUMIDITY RANGE	40% TO 80% (NOTE2) 			STORAGE HUMIDITY RANGE	40% TO 70% (NOTE3) 
	VOLTAGE	250V AC	UL·CSA RATING 	30V AC	APPLICABLE CONTACT 	DF11-EP2428PC (F) DF11-EP2428PC (F) A
	CURRENT	2 A		2 A	APPLICABLE CABLE 	UL1061, 1007 AWG24 TO 28
	APPLICABLE CONNECTOR 	DF11-*DS-2C				

SPECIFICATIONS

ITEM	TEST METHOD	REQUIREMENTS	QT	AT
------	-------------	--------------	----	----




CONSTRUCTION

GENERAL EXAMINATION	VISUALLY AND BY MEASURING INSTRUMENT.	ACCORDING TO DRAWING.	X	X
MARKING	CONFIRMED VISUALLY.		X	X


ELECTRIC CHARACTERISTICS

INSULATION RESISTANCE	500 V DC.	1000 MΩ MIN.	X	-
VOLTAGE PROOF	650 V AC FOR 1 min.	NO FLASHOVER OR BREAKDOWN.	X	-

MECHANICAL CHARACTERISTICS

MECHANICAL OPERATION 	30 TIMES INSERTIONS AND EXTRACTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
VIBRATION 	FREQUENCY 10 TO 55 Hz, SINGLE AMPLITUDE 0.75 mm, AT 2 h, FOR 3 DIRECTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
SHOCK 	490 m/s ² DURATION OF PULSE 11 ms AT 3 TIMES FOR 3 DIRECTIONS.	NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-


ENVIRONMENTAL CHARACTERISTICS


RAPID CHANGE OF TEMPERATURE 	TEMPERATURE -55→ 5 TO 35→+85→ 5 TO 35 °C TIME 30→ 5 MAX → 30→ 5 MAX min UNDER 5 CYCLES.	① INSULATION RESISTANCE: 1000MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-
DAMP HEAT (STEADY STATE)	EXPOSED AT 40 ± 2 °C, 90 TO 95 %, 96 h.	① INSULATION RESISTANCE: 1000MΩ MIN. ② NO DAMAGE, CRACK OR LOOSENESS OF PARTS.	X	-

REMARKS

NOTE 1: INCLUDING THE TEMPERATURE RISE BY CURRENT.

NOTE 2:NO CONDENSING. 

NOTE 3:APPLY TO THE CONDITION OF LONG TERM STORAGE FOR UNUSED PRODUCTS BEFORE PCB ON BOARD, AFTER PCB BOARD, OPERATING TEMPERATURE AND HUMIDITY RANGE IS APPLIED FOR INTERIM STORAGE DURING TRANSPORTATION. 

COUNT	DESCRIPTION OF REVISIONS	DESIGNED	CHECKED	DATE
 13	DIS-H-008583	MI. SAKIMURA	HK. UMEHARA	14. 03. 25



REMARKS

NOTE 1:INCLUDING THE TEMPERATURE RISE BY CURRENT.

APPROVED	KJ. KATAYOSE	05. 01. 05
CHECKED	TY. OMA	05. 01. 05
DESIGNED	IO. DENPOUYA	05. 01. 05
DRAWN	IO. DENPOUYA	05. 01. 05

Unless otherwise specifid , refer to IEC 60512.

Note QT:Qualification Test AT:Assurance Test X:Applicable Test	DRAWING NO.	ELC4-081880-01
--	-------------	----------------

	SPECIFICATION SHEET	PART NO.	DF11-*DEP-2C	
	HIROSE ELECTRIC CO., LTD.	CODE NO.	CL543	 1/1