



PANEL THICKNESS	X dimension
0.75-1.25 [.030-.049]	19.2-0.1 [.756]
1.25-2.0 [.049-.079]	19.4-0.1 [.764]
2.0-3.0 [.079-.118]	19.8-0.1 [.780]



SWITCH FUNCTION		
POS. 1	POS. 2	POS. 3
<ON>	OFF	<ON>
1-1a	OPEN	1-1b

< >=MOMENTARY



- NOTES:
- ALL DIMENSIONS IN MM [INCH]
 - GENERAL TOLERANCE: X.X=±0.4
X.XX=±0.25
 - TERMINAL NUMBERS FOR REF ONLY
 - RATING: 15A @ 125VAC OR
8A @ 250VAC
 - MATERIALS: TERMINALS: Silver Plated Copper Alloy
CONTACTS: Coin Silver, Silver Plated
 - ELECTRIC LIFE: 10,000 cycles
 - CONTACT RESISTANCE: <20 Mega-OHM
 - INSULATION RESISTANCE: >1000 Mega-OHM
 - DIELECTRIC STRENGTH: >1500 V 1 minute
>3000 V between poles
 - ▲ DENOTES CRITICAL PARAMETER.

E-SWITCH®

A	14112	RELEASED FOR PRODUCTION	6/23/04	AR
REV.	ECN No.	DESCRIPTION	DATE	CHKD

TITLE	R1966IBLKREDEF			
-------	----------------	--	--	--

SCALE	DATE	DR	DWG	REV
1.5:1	6/23/04	AR	M306208	A

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED