

**PTSM 0,5/ 4-HH-2,5-THR R32**

Order No.: 1778641

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1778641>

Header, Nominal current: 6 A, Rated voltage (III/2): 160 V, Number of positions: 4, Pitch: 2.5 mm, Color: black, Metal surface: Sn, Assembly: SMD/THT/THR

**Commercial data**

|                          |                     |
|--------------------------|---------------------|
| GTIN (EAN)               |                     |
| sales group              | E430                |
| Pack                     | 500 pcs.            |
| Customs tariff           | 85369010            |
| Catalog page information | Page 185 (NTK-2010) |

**Product notes**

WEEE/RoHS-compliant since:  
09/17/2009



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****Dimensions / positions**

|                     |        |
|---------------------|--------|
| Length              | 7.5 mm |
| Pitch               | 2.5 mm |
| Dimension a         | 7.5 mm |
| Number of positions | 4      |

|                |              |
|----------------|--------------|
| Pin dimensions | 0,6 x 0,6 mm |
| Pin spacing    | 2.50 mm      |
| Hole diameter  | 1.1 mm       |

#### Technical data

|                                     |                    |
|-------------------------------------|--------------------|
| Range of articles                   | PTSM 0,5/..-HH-THR |
| Insulating material group           | IIIa               |
| Rated surge voltage (III/3)         | 2.5 kV             |
| Rated surge voltage (III/2)         | 2.5 kV             |
| Rated surge voltage (II/2)          | 2.5 kV             |
| Rated voltage (III/2)               | 160 V              |
| Rated voltage (II/2)                | 160 V              |
| Connection in acc. with standard    | EN-VDE             |
| Nominal current $I_N$               | 6 A                |
| Nominal voltage $U_N$               | 50 V               |
| Maximum load current                | 6 A                |
| Insulating material                 | LCP                |
| Inflammability class acc. to UL 94  | V0                 |
| Nominal voltage, UL/CUL Use Group B | 150 V              |
| Nominal current, UL/CUL Use Group B | 6 A                |

#### Certificates / Approvals




Certification


CUL, UL

### Diagrams/Drawings

Drilling plan/solder pad geometry



Dimensioned drawing



**Address**

PHOENIX CONTACT Inc., USA  
586 Fulling Mill Road  
Middletown, PA 17057, USA  
Phone (800) 888-7388  
Fax (717) 944-1625  
<http://www.phoenixcon.com>



© 2011 Phoenix Contact  
Technical modifications reserved;