

## Specification Sheet

Part Number: 596-00653

RATED MAX POWER-POINT CURRENT	<input type="text"/>
RATED MAX POWER-POINT VOLTAGE	<input type="text"/>
MAXIMUM SYSTEM VOLTAGE	<input type="text"/>
MAXIMUM CIRCUIT CURRENT	<input type="text"/>
MAX RATED OUTPUT CURRENT OF THE CHARGE CONTROLLER IF INSTALLED	<input type="text"/>

Solar Label, Printable, DC Module, 4.0" x 2.0", PET, Red, 25/roll

Article Number	596-00653
Type	DC2011-1
Color	Red (RD)
Features & Benefits	<ul style="list-style-type: none"><li>• Made with UV-stable inks and materials for durability and weather resistance.</li><li>• Polyester is resistant to chemicals and solvents and will remain legible in dirty environments.</li><li>• High abrasion and scuff resistance for high-performance labeling.</li><li>• Meets NEC &amp; IFC standards for printed text, character height, color and outdoor UV stability to pass inspections.</li></ul>
Quantity Per	roll

### Product Description

HellermannTyton pre-printed Solar Rating labels are designed to meet the requirements of the National Electrical Code and the International Fire Code as well as being acceptable to the Authority Having Jurisdiction (AHJ). Labels are made with durable UV-stable materials and adhesives that are designed to stick to both baked enamel and powder coat surfaces. Where applicable, labels are made using reflective materials for first responder safety. Some pre-printed labels are printable using a thermal transfer printer when variable voltage or series data must be printed and displayed.

<b>Short Description</b>	Solar Label, Printable, DC Module, 4.0" x 2.0", PET, Red, 25/roll
<b>Global Part Name</b>	DC2011-1-840/926-RD
<b>Technical Description</b>	Printable Solar Label, DC MODULE LABEL, 4.0" X 2.0", Red
<b>Width W (Imperial)</b>	2.0
<b>Width W (Metric)</b>	50.8
<b>Thickness T (Metric)</b>	64.0
<b>Height H (Imperial)</b>	4.0
<b>Height H (Metric)</b>	101.6
<b>Material</b>	Type 840/926, Polyester (PET), UV stable, clear Polyester laminate
<b>Material Shortcut</b>	840/926
<b>Adhesive</b>	Acrylic
<b>Halogen free</b>	No
<b>Adhesive Operating Temperature</b>	-40°F to +302°F (-40°C to +150°C)
<b>Operating Temperature (Metric)</b>	-40°F to +302°F (-40°C to +150°C)
<b>Reach Complaint(Article 33)</b>	Yes

**ROHS Complaint** Yes

**Certification/Specification WEB** UL 969

**UL Recognized (US)** Yes

**Package Quantity(Imperial)** 50

**Package Quantity (Metric)** 50

**Customs Number** 3919102055

**Labels per Column** 1

**Labels per Row** 1

**Weight (Metric)** 0.521

**Weight (Imperial)** 1.14