

	1	2	3	4	5	6	7	
A								
B								
C								
D								
E								
F								
G	<p>Tolerance</p> <p>X. ±0.50</p> <p>XX ±0.30</p> <p>XXX ±0.10</p> <p>XX° ±1°</p>							
H	1	2	3	4	5	6	7	
Modification					Date	Name	P/N	
					Drawn	06.12.06	Hellwig	A-TB500-V303R
					<p>ASSMANN</p> <p>WSW Components</p>		<p>Drawing-No.</p> <p>ASS 0653 CO</p> <p>Replace</p>	<p>Sheet</p> <p>1/1</p> <p>Sheet</p>
<p>Technical Data:</p> <p>Material:</p> <ul style="list-style-type: none"> ● Contact(metal housing): Brass Machined(option) ● Terminal screw: Steel galvanized and achromatized or Nickel plated or Tin plated(standard)(option) ● Solder Pin: Brass with Tin plated ● Insulator body/housing: Polyamide(Glass filled)(UL94V-0) <p>Electrical</p> <ul style="list-style-type: none"> ● Voltage rating: 300VAC ● Current rating: 10 Amps/way max ● Contact resistance: 20mΩ(max) ● Insulation resistance: 5000MΩ/1000V ● Withstanding Voltage: 1500VAC(1min) Test time=60sec/1pcs ● Wire range: 12-22AWG <p>Mechanical:</p> <ul style="list-style-type: none"> ● Torque: 4kgf.cm/M2.5 ● Operating temperature: -33°C to +120°C ● Soldering reliability: Test temperature= 250°C±10°C 5 seconds max 								