



PIN ASSIGNMENT	
P1	P2
1	1
2	2
3	3
4	4
5	5
6	6
7	7
8	8
9	9
Shell	Shell

- Electrical test:
1. 100% short, open, miss wire test
 2. Conduct resistance: 2 Ohm max.
 3. Insulator resistance: 5Mohm min.
 4. Hi-Pot: 300V DC/10ms

⑧	PE Bag	1pcs	Clear Print black "MADE IN CHINA"+ "1PC"
⑦	Tie	1pcs	White tie
⑥	Outermold	NA	PVC: 45P Beige(BG002)
⑤	Innermold	NA	LD-PE
④	Tube	2pcs	Heat shrink tube black OD:Ø1.5"L:15mm
③	Screw	4pcs	Screw #4-40UNC D-E L=32.5mm Nickel plated Insulator color:Beige(BG002)
②	CONN	2pcs	DB 9Pin Female, Pin:G/F Shell:Nickel Insulator color:Blue solder type
①	Cable	1pcs	No UL 28AWG(7/0.12TC)*9C+D+AL/MYlar Jacket PVC, Beige(BG002) OD:5.0mm

RoHS compliant
Unit:mm

Scale	Free	Customer-No.
TOLERANCE		ASSMANN WSW-No.
		AK152-2
DIM	TOL	Drawing-No.
		ASS 7604 CA
Angle	TOL	Replace
		rev00
		Sheet
Id.	Drawn	
	Modification	
Date	05.04.2016	
Name	Amy	

ASSMANN
components

1 2 3 4 5 6 7

A B C D E F G H