



HARTING PushPull, type acc. to IEC 61 076-3-106 variant 4
cable to cable housing

Features

- HARTING PushPull technology
- Ideal for prototyping
- Can be combined with panel feed-throughs for power, data and signal

Technical characteristics

| | |
|----------------------------|---|
| Locking | PushPull technology acc. to IEC 61076-3-106 variant 4 |
| Degree of protection | IP65 / IP67 |
| Outer cable diameter | 6.5 ... 9.5 mm |
| Mating cycles | min. 750 |
| Temperature range | -40 °C ... +70 °C |
| Housing material | Plastic, black |
| Flammability acc. to UL 94 | V0 |

| Identification | Part number | Drawing | Dimensions in mm |
|--|--|---|------------------|
| HARTING PushPull cable to cable housings, plastic (Order housing bulkhead mounting and insert separately) for outer cable diameter 6.5 ... 9.5 mm | 09 45 345 0000 | 2X M2.5x10 self tapping screws according to EN ISO 7092 | |
| HARTING PushPull bulkhead housings, plastic (Order housing bulkhead mounting and insert separately) | 09 45 345 0001 | 2X M2.5x10 self tapping screws according to EN ISO 7092 | |
| Suitable bulkhead housing, plastic for RJ45 / Signal | 09 45 545 0028 | | |
| Inserts for RJ45 / Signal RJ 45: 8-poles, Cat. 6 / class E _A Ha-Vis preLink® set AWG 22/23 HARTING RJ Industrial® cable jack with IDC termination AWG 22-24, 8-poles AWG 24-28, 8-poles AWG 22-24, 4-poles, Cat. 5 | 20 82 001 0001 09 45 545 1562 09 45 545 1561 09 45 545 1120 | | |
| Signal: 10-poles, 50 V / 5 A* | 09 45 545 9010 | | |

* Order D-Sub crimp male contacts separately (see pages 02.19 and 02.20)