

# RAD-ISM-2400-ANT-PAN- 8-0


Order No.: 2867610



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2867610>

Panel antenna, degree of protection IP55, 8 dBi gain, linear vertical, SMA (female), impedance 50 ohms, apex angle h/v 75°/70°

## Commercial data

GTIN (EAN)	 4 017918 938994
sales group	H179
Pack	1 pcs.
Customs tariff	85177019
Catalog page information	Page 535 (IF-2009)

## Product notes

WEEE/RoHS-compliant since:  
01/08/2008



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### General data

Frequency range	2.3 GHz ... 2.8 GHz
Horizontal beamwidth	75 °
Vertical beamwidth	70 °
Impedance	50 Ω
Gain	8 dBi

Wind load	15 N (at 160 km/h)
Type of connection	SMA (female)
Degree of protection	IP55
Ambient temperature (operation)	-40 °C ... 75 °C
Ambient temperature (storage/transport)	-40 °C ... 75 °C
Width	80 mm
Height	100 mm
Length	20 mm

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;