



General ordering data

| | |
|------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Order No. | 1672240000 |
| Part designation | BLZF 5.08/9/270 SN SW |
| Version | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 9, 270°, Box |
| EAN | 4008190433956 |
| Qty. | 50 pc(s). |

System parameters

| | |
|-------------------------------------------|-----------------------------------------------------|
| Conductor connection system | Tension clamp connection |
| Outgoing direction of conductor | 270° |
| Pitch | 5.08 mm |
| Pitch in inch | 0.2 inch |
| No. of poles | 9 |
| No. of rows | 1 |
| Screwdriver blade | 0.6 x 3.5 |
| Screwdriver blade standard | DIN 5264-A |
| Stripping length | 10 mm |
| L1 in mm | 40.64 mm |
| L1 in inch | 1.6 inch |
| Electric shock protection to DIN VDE 0470 | Finger-safe plugged/ back-of-hand-safe unplugged |

System parameters

Material data

| | |
|---------------------------|---------------------|
| Insulating material | PBT |
| Colour | black |
| colour chart | Similar to RAL 9011 |
| Insulating material group | IIIa |
| Flammability class UL 94 | V-0 |
| CTI | >= 200 |
| Contact base material | Copper alloy |
| Contact surface | tinned |

Connectable conductors

| | |
|---------------------------------------------------|----------------------|
| Clamping range, min. | 0.13 mm ² |
| Clamping range, max. | 3.31 mm ² |
| AWG, min. | 26 |
| AWG, max. | 12 |
| Solid, min. H05(07) V-U | 0.2 mm ² |
| Solid, max. H05(07) V-U | 2.5 mm ² |
| Flexible, min. H05(07) V-K | 0.2 mm ² |
| Flexible, max. H05(07) V-K | 2.5 mm ² |
| With wire end ferrule, acc. to DIN 46 228/1, min. | 0.2 mm ² |
| With wire end ferrule, acc. to DIN 46 228/1, max. | 1.5 mm ² |
| w. plastic collar ferrule, DIN 46228 pt 4, min. | 0.2 mm ² |
| w. plastic collar ferrule, DIN 46228 pt 4, max. | 1.5 mm ² |
| Gauge to EN 60999 a x b; ø | 2.8 mm x 2.0 mm; |

DIN IEC rating data

| | |
|--------------------------------------------------------------------------------|-------------------|
| Rated current, min. No. pins (Tu=20°C) | 16.5 A |
| Rated current, max. No. pins (Tu=20°C) | 12.5 A |
| Rated current, min. No. pins (Tu=40°C) | 14 A |
| Rated current, max. No. pins (Tu=40°C) | 11 A |
| Rated voltage for overvoltage class/pollution severity II/2 | 400 V |
| Rated voltage for overvoltage class/pollution severity III/2 | 320 V |
| Rated voltage for overvoltage class/pollution severity III/3 | 250 V |
| Rated impulse withstand voltage for overvoltage class/pollution severity II/2 | 4 kV |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/2 | 4 kV |
| Rated impulse withstand voltage for overvoltage class/pollution severity III/3 | 4 kV |
| Short-time withstand current resistance | 3 x 1s with 120 A |

CSA rating data

| | |
|------------------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |
| AWG conductor (field wiring), min. | 26 |
| AWG conductor (field wiring), max. | 12 |

UL 1059 rating data

| | |
|-----------------------------|-------|
| Rated voltage (Use group D) | 300 V |
| Rated current (Use group D) | 10 A |
| AWG conductor, min. | 26 |
| AWG conductor, max. | 12 |

Approvals

Approvals institutes



Classifications

| | |
|------------|-------------|
| ETIM 2.0 | NK |
| ETIM 3.0 | EC001284 |
| eClass 4.1 | 27-26-07-01 |
| eClass 5.0 | 27-26-07-01 |
| eClass 5.1 | 27-26-07-04 |

Similar products

| Order No. | Part designation | Version |
|------------|-----------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1671940000 | BLZF 5.08/2/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 2, 270°, Box |
| 1672170000 | BLZF 5.08/2/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 2, 270°, Box |
| 1671950000 | BLZF 5.08/3/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 3, 270°, Box |
| 1672180000 | BLZF 5.08/3/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 3, 270°, Box |
| 1671960000 | BLZF 5.08/4/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 4, 270°, Box |
| 1672190000 | BLZF 5.08/4/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 4, 270°, Box |
| 1671970000 | BLZF 5.08/5/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 5, 270°, Box |
| 1672200000 | BLZF 5.08/5/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 5, 270°, Box |
| 1671980000 | BLZF 5.08/6/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 6, 270°, Box |

| | | |
|------------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1672210000 | BLZF 5.08/6/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 6, 270°, Box |
| 1671990000 | BLZF 5.08/7/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 7, 270°, Box |
| 1672220000 | BLZF 5.08/7/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 7, 270°, Box |
| 1672000000 | BLZF 5.08/8/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 8, 270°, Box |
| 1672230000 | BLZF 5.08/8/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 8, 270°, Box |
| 1672010000 | BLZF 5.08/9/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 9, 270°, Box |
| 1672020000 | BLZF 5.08/10/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 10, 270°, Box |
| 1672250000 | BLZF 5.08/10/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 10, 270°, Box |
| 1672030000 | BLZF 5.08/11/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 11, 270°, Box |
| 1672260000 | BLZF 5.08/11/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 11, 270°, Box |
| 1672040000 | BLZF 5.08/12/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 12, 270°, Box |
| 1672270000 | BLZF 5.08/12/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 12, 270°, Box |
| 1672050000 | BLZF 5.08/13/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 13, 270°, Box |
| 1672280000 | BLZF 5.08/13/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 13, 270°, Box |
| 1672060000 | BLZF 5.08/14/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 14, 270°, Box |
| 1672290000 | BLZF 5.08/14/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 14, 270°, Box |
| 1672070000 | BLZF 5.08/15/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 15, 270°, Box |

| | | |
|------------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1672300000 | BLZF 5.08/15/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 15, 270°, Box |
| 1672080000 | BLZF 5.08/16/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 16, 270°, Box |
| 1672310000 | BLZF 5.08/16/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 16, 270°, Box |
| 1672090000 | BLZF 5.08/17/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 17, 270°, Box |
| 1672100000 | BLZF 5.08/18/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 18, 270°, Box |
| 1672320000 | BLZF 5.08/17/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 17, 270°, Box |
| 1672330000 | BLZF 5.08/18/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 18, 270°, Box |
| 1672110000 | BLZF 5.08/19/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 19, 270°, Box |
| 1672340000 | BLZF 5.08/19/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 19, 270°, Box |
| 1672120000 | BLZF 5.08/20/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 20, 270°, Box |
| 1672350000 | BLZF 5.08/20/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 20, 270°, Box |
| 1672130000 | BLZF 5.08/21/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 21, 270°, Box |
| 1672360000 | BLZF 5.08/21/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 21, 270°, Box |
| 1672140000 | BLZF 5.08/22/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 22, 270°, Box |
| 1672370000 | BLZF 5.08/22/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 22, 270°, Box |
| 1672150000 | BLZF 5.08/23/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 23, 270°, Box |
| 1672380000 | BLZF 5.08/23/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 23, 270°, Box |

| | | |
|------------|------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------|
| 1672160000 | BLZF 5.08/24/270 SN OR | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 24, 270°, Box |
| 1672390000 | BLZF 5.08/24/270 SN SW | PCB plug-in connector, Female connectors, Tension clamp connection, Clamping range, max.: 3.31 mm ² , Pitch: 5.08 mm, No. of poles: 24, 270°, Box |