



**100W Constant Current LED Driver
PDA100W LED Power Supply with 0-10V Dimming**



Features

- High Efficiency
- UL8750 Compliant
- Brownout Protection
- OVP, Short and Open Circuit Protections
- 0-10V Dimming
- IP65 Rated
- Wide Operating Temperature Range
- 108-305VAC Input Range
- 5 Year Warranty

Applications

- General Lighting
- Street Lighting
- Outdoor Lighting
- Architectural Lighting

Safety Approvals

- cUL/UL

Mechanical Characteristics

- Length: 241mm (9.49in)
- Width: 59mm (2.32in)
- Height: 39mm (1.54in)
- Weight: TBD

Output Specifications

Model	DC Output Voltage			Output Current	Output Power
	Min.	Typ.	Max.		
PDA100W-700GD	82V	-	143V	700mA	100W
PDA100W-1A0GD	58V	-	100V	1000mA	100W

Phihong is not responsible for any error, and reserves the right to make changes without notice. Please visit our website at www.phihong.com for the most up-to-date specifications and contact information.

Input:

AC Input Voltage Range
108VAC to 304VAC

AC Input Frequency
47~63Hz

Maximum Input Current
≤ 1.26A

Leakage Current
0.75mA maximum at 277VAC Input

Inrush Current
< 80A

OUTPUT:
Power Factor
≥ 0.9

Output Current Ripple
<105mA (p-p)

Efficiency
88% at 120VAC
91% at 277VAC

Turn-on Delay Time
<0.5s maximum at nominal AC Power ON

Environmental:

Temperature

Operation -40 to +50°C
Non-operation -40 to +90°C
Case Temperature <85°C
Operating Humidity 5 to 98%

Dimming Control
0-10VDC

Dimming Grounding

Dim(-) and Vout(-) must never be connected together to ensure proper operation and isolation requirements

EMC

EN55015/CISPR 15/FCC 47 Part 15/18 Class A

Immunity

IEC61000-4-2
IEC61000-4-3
IEC61000-4-4
IEC61000-4-5
IEC61000-4-6
IEC61000-4-8
IEC61000-4-11
IEC61000-3-2 Class C

Input Over Current Protection

The input power line will be fused with a 6.3A fuse

Short-Circuit Protection

The PSU will withstand a short circuit across the outputs without damage

Over Temperature Protection

The load will drop by 50% automatically if the case temperature exceeds the recommended limit

Dielectric Withstand (Hi-pot) Test

Primary to secondary: 4242VDC for 1 minute, 5.5mA

Insulation Resistance

Primary to secondary: >5M Ohm 500VDC, 1 Minute

Wire Connections

Position	Terminal Color	Specification	Length
Line	Black	AWG18 Solid Wire	390mm
Neutral	White	AWG18 Solid Wire	390mm
Ground	Green/Yellow	AWG18 Solid Wire	390mm
Vout+	Red	AWG18 Solid Wire	390mm
Vout-	Blue	AWG18 Solid Wire	390mm
20V	Yellow	AWG22 Solid Wire	390mm
Dim+	Violet	AWG22 Solid Wire	390mm
Dim-	Grey	AWG22 Solid Wire	390mm

Warranty

5 Years

