

## Specification Sheet

Part Number: T50R0PPC2



Polypropylene Cable Tie, 8" Long, 25lb Tensile Strength, PP, Black, 100/pkg

Article Number	111-04928
Type	T50R
Color	Black (BK)
Features & Benefits	<ul style="list-style-type: none"><li>• Polypropylene cable ties provide excellent resistance to chemicals and salts.</li><li>• Inside serrations allow for strong hold on cables and wire bundles.</li><li>• Head design provides high tensile strength with very low insertion force.</li><li>• Bent tail ensures a quick and simple installation.</li></ul>
Quantity Per	bag

### Product Description

HellermannTyton standard cable ties feature inside serrations providing a positive hold onto wire and cable bundles. The head design guarantees high tensile strength, as well as a low insertion force. The bent tail design allows quick and simple installations by hand. For high volume applications, tensioning tools are available to ensure consistent and safe installation.

<b>Short Description</b>	Polypropylene Cable Tie, 8" Long, 25lb Tensile Strength, PP, Black, 100/pkg
<b>Global Part Name</b>	T50R-PP-BK
<b>Minimum Tensile Strength (Imperial)</b>	25.0
<b>Minimum Tensile Strength (Metric)</b>	111.0
<b>Length L (Imperial)</b>	8.0
<b>Length L (Metric)</b>	202.0
<b>Identification Plate Position</b>	none
<b>Releasable Closure</b>	No
<b>Tie Closure</b>	plastic pawl
<b>Variant</b>	Inside Serrated
<b>Width W (Imperial)</b>	0.18
<b>Width W (Metric)</b>	4.6
<b>Bundle Diameter Min (Imperial)</b>	0.06
<b>Bundle Diameter Min (Metric)</b>	1.5
<b>Bundle Diameter Max (Imperial)</b>	1.75
<b>Bundle Diameter Max (Metric)</b>	44.5
<b>Thickness T (Imperial)</b>	0.05

**Thickness T (Metric)** 1.2

**Material** Polypropylene (PP)

**Material Shortcut** PP

**Flammability** UL 94 HB

**Halogen free** Yes

**Operating Temperature (Metric)** -40°F to +239°F (-40°C to +115°C)

**Reach Complaint(Article 33)** Yes

**ROHS Complaint** Yes

**Package Quantity(Imperial)** 100

**Package Quantity (Metric)** 100

**Customs Number** 3926909987

**Content Unit(BMEcat)** pcs.

